

Sugar Mover

Material Safety Data Sheet (rev.03/27)

**SECTION I PRODUCT IDENTIFICATION**

**NFPA HAZARD RATINGS**  
 HEALTH HAZARD 3      FIRE HAZARD 1      REACTIVITY 0  
**SARA/ TITLE III HAZARD CATEGORIES**

Company Name:	STOLLER USA, INC.
Address:	4001 W. Sam Houston Parkway, N., Suite 100 Houston, Texas 77043-1226 U.S.A.
Emergency Phone Number:	CHEMTREC: In the U.S. and Canada call Toll- free: 1(800)424-9300 From other countries call collect 1-713-527-3887
Phone Number for Information:	1(800)539-5283 or 1(713)461-1493
Chemical Family:	Solution of Organic Bases and Boron
Chemical Name & Synonyms:	Liquid Fertilizer containing Boron and amines
Formula:	Proprietary
Trade name & Synonyms:	SUGAR MOVER

**SECTION II PHYSICAL AND CHEMICAL CHARACTERISTICS**

INGREDIENTS:	CAS#	Approx. %	TLV
Copper Hydroxide	20427-59-2	<5	1mg/ m3 as Cu
Orthoboric Acid	10043-35-3	50-60	N/ E
Dimethyl Aminopropylamine	109-55-7	<5	N/ E
Monoethanolamine	141-43-5	15-25	3 ppm

**SECTION III PHYSICAL AND CHEMICAL CHARACTERISTICS**

<b>BOILING POINT:</b>	230°F	<b>VAPOR PRESSURE (mm/ Hg):</b>	
<b>MELTING POINT:</b>	N/ A	<b>VAPOR DENSITY (air = 1):</b>	N/ A
<b>SPECIFIC GRAVITY:</b>	1.30	<b>REACTIVITY IN WATER:</b>	-0-
<b>SOLUBILITY IN WATER:</b>	100%	<b>EVAPORATION RATE:</b>	N/ A
<b>APPEARANCE AND ODOR:</b>	Clear blue liquid- with no odor		
<b>PERCENT VOLATILE BY VOLUME:</b>			N/ A

**SECTION IV FIRE AND EXPLOSION DATA**

<b>FLASH POINT:</b>	Not Established (N/ E)	<b>LEL:</b>	<b>UEL:</b>
<b>FLAMMABLE LIMITS:</b>	N/ E		
<b>EXTINGUISHER MEDIA:</b>	In case of fire use: Carbon Dioxide (CO <sub>2</sub> ), Dry Chemical, Alcohol Foam.		
<b>SPECIAL FIRE FIGHTING PROCEDURES:</b>	Firefighters should wear butyl rubber boots and clothing.		
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b>	N/ A		

**SECTION V****PHYSICAL HAZARDS (REACTIVITY DATA)**

<b>STABILITY:</b>	Stable: Yes      Unstable:
<b>CONDITIONS TO AVOID:</b>	N/A
<b>INCOMPATIBILITY, MATERIALS TO AVOID:</b>	Oxidizing Agents (perchlorates, nitrates, nitrites, etc.) and high concentrations of mineral acids.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Carbon Monoxide, Nitrogen Oxide, Carbon Dioxide and Nitric Acid possible in a fire. Ammonia and Hydrogen Cyanide under extreme h
<b>MAY OCCUR:</b>	<b>WILL NOT OCCUR: X</b>

**SECTION VI****HEALTH HAZARDS**

- A. **EXPOSURE LIMITS:** No Limits Established
- B. **CARCINOGEN OR POTENTIAL CARCINOGEN:**
- C. **EFFECTS OF OVEREXPOSURE:**
1. **ACUTE:**  
**EYES:** Contact with product may cause severe irritation and possible irreversible damage.  
**SKIN:** Harmful if absorbed through broken skin. Large doses may cause liver and kidney damage. May cause, discomfort, injury and death unless treated promptly.  
**INHALATION:** Prolonged exposure to low concentration of vapors may cause sore throat and headache which are temporary.  
**INGESTION:** May cause malaise, nausea, gastrointestinal damage, or even death.
  2. **CHRONIC:** Prolonged or repeated inhalation overexposure may cause bronchitis or pneumonia.
- D. **EMERGENCY FIRST AID PROCEDURES:**
- EYES:** Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.
- SKIN:** Remove product & immediately flush affected area with water for 15 minutes. Do not apply greases or ointments, Launder contaminated clothing.
- INHALATION:** Move patient to fresh air. Supplemental oxygen may be indicated. Assure mucous does not obstruct airway. Call Physician.
- INGESTION:** If swallowed, call a physician immediately. Do not induce vomiting.
- E. **ANIMAL TOXICITY DATA:**
- Oral LD<sub>50</sub> (rat): 1640 mg/ kg  
Inhalation LC<sub>50</sub>(rat): >21 mg/ Liter/ Hr (No deaths) (Estimate)  
Dermal LD<sub>50</sub> (rabbit): No Data

**SECTION VII****SPECIAL PRECAUTIONS & SPILL/ LEAK PROCEDURES**

- HANDLING AND STORAGE:** Keep containers closed and away from oxidizing agents. Store only in shipping container: Pails (HDPE, PVC), Drums (Polyethylene) and Mini Bulk tanks (Polyethylene). Bulk material should be stored in Polyethylene Tanks with PVC fittings.
- STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED:** It is necessary to contain spill into the smallest area possible by diking, etc., replace liquid into plastic container. If liquid is absorbed onto dry carrier such as soil or absorbent material, then this material should be held in a dry contained area.
- WASTE DISPOSAL METHODS:** Liquid should be applied to the soil as a fertilizer not to exceed 3 gallons per acre. Product absorbed onto dry carrier should be applied to soil as a fertilizer not to exceed 50 lbs. per acre.

**SECTION VIII****SPECIAL PROTECTION / CONTROL MEASURES**

- RESPIRATORY PROTECTION:** As required by emergency situation, use an OSHA or NIOSH approved respirator.
- VENTILATION:** Work outdoors in open or well- ventilated area with this product.
- PROTECTIVE GLOVES:** Wear latex, vinyl or butyl rubber gloves.
- EYE PROTECTION:** Use splashproof eye goggles. It is best to wear a full face shield. Eye wash should be available.
- OTHER SPECIAL CLOTHING/ EQUIPMENT:** Wear clothing that covers the exposed skin area as much as possible.
- WORK/ HYGIENIC PRACTICES:** Wash thoroughly after handling. Also wash clothing.

**SECTION IX****ENVIRONMENTAL EFFECTS DATA**

---

The available data on this plant nutrient material does not indicate any undue hazard to the environment under anticipated use and storage. Any waste due to spillage or leakage should be contained and disposed of as Fertilizer (see above under Waste Disposal Methods). Due to its nutritional value, may contribute to eutrophication in bodies of water.

**SECTION X****TRANSPORTATION DATA**

---

**PROPER SHIPPING NAME:** SUGER MOVER

**DOT HAZARD CLASS:** NON- REGULATED MATERIAL

**PLACARD:** N/ A

Stoller Enterprises, Inc., believes the information contained in this material safety data sheet is accurate based on the information supplied by reputable suppliers of our raw materials. The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.