

MICRO PLUS™ IRON

Material Safety Data Sheet (rev.03/27)

SECTION I PRODUCT IDENTIFICATION

	NFPA HAZARD RATINGS
	HEALTH HAZARD 2 FIRE HAZARD 0 REACTIVITY 0
	SARA/ TITLE III HAZARD CATEGORIES (See Section IX)
	Immediate (ACUTE) Health: NO Reactive Hazard: NO
	Delayed (Chronic) Health: NO Fire Hazard: NO Sudden Release of Pressure: NO
Company Name:	STOLLER USA, INC.
Address:	4001 W. Sam Houston Parkway, N., Suite 100 Houston, Texas 77043-1226 U.S.A.
Emergency Phone Number:	CHEMTREC: In the U.S. and Canada call Toll- free: 1(800)424-9300 From other countries call collect: 1+(703)527-3887
Phone Number for Information:	1(800)539-5283 or 1(713)461-1493
Chemical Family:	Iron solution
Chemical Name & Synonyms:	Ferrous Chloride
Formula:	Proprietary
Trade name & Synonyms:	MICRO PLUS IRON

SECTION II PHYSICAL AND CHEMICAL CHARACTERISTICS

INGREDIENTS:	CAS#	Approx. %	TLV
Copper Chloride	7758-94-3	40%	1 mg/ m ³ (TWA) as Iron

SECTION III PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT:	Not Established	VAPOR PRESSURE (mm/ Hg):	
MELTING POINT:	N/ A	VAPOR DENSITY (air = 1):	N/ E
SPECIFIC GRAVITY:	1.26	REACTIVITY IN WATER:	-0-
SOLUBILITY IN WATER:	100%	EVAPORATION RATE:	
APPEARANCE AND ODOR:	Reddish- brown liquid - with no odor		

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT:	N/ A		
FLAMMABLE LIMITS:	N/ A	LEL: N/ A	UEL: N/ A
EXTINGUISHER MEDIA:	In case of fire use: Carbon Dioxide (CO ₂), Dry Chemical, Alcohol foam		
SPECIAL FIRE FIGHTING PROCEDURES:	Firefighters should wear butyl rubber boots and clothing		
UNUSUAL FIRE AND EXPLOSION HAZARDS:	N/ A		

SECTION V**PHYSICAL HAZARDS (REACTIVITY DATA)**

STABILITY:	Stable: Yes Unstable:
CONDITIONS TO AVOID:	N/ A
INCOMPATIBILITY, MATERIALS TO AVOID:	Oxidizing Agents (perchlorates, nitrates, nitrites, etc.) and high concentrations of mineral acids.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon Monoxide, Nitrogen Oxide, Carbon Dioxide and Nitric Acid possible in a fire. Toxic chloride fumes under extreme heat as in a fire.
MAY OCCUR:	WILL NOT OCCUR: X

SECTION VI**HEALTH HAZARDS**

- A. EXPOSURE LIMITS:**
1. OSHA Permissible Exposure Limit (PEL): N/ E
2. Threshold Limit Value (TLV): N/ E
- B. CARCINOGEN OR POTENTIAL CARCINOGEN:**
- C. EFFECTS OF OVEREXPOSURE:**
1. **ACUTE:**
EYES: Prolonged exposure to product vapors may cause eye irritation and eye damage can occur.
SKIN: May cause malaise, discomfort, injury and death unless treated promptly.
INHALATION: Prolonged exposure to low concentrations of vapors may cause sore throat and headache which are temporary.
INGESTION: May cause malaise, nausea, death unless treated promptly.
2. **CHRONIC:** Copper poisoning is typified by hepatic cirrhosis, lung, pancreas and kidney damage.
- D. EMERGENCY FIRST AID PROCEDURES:**
EYES: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Call a physician.
SKIN: Immediately flush affected area with water for 15 minutes. Do not apply greases or ointments.
INHALATION: Move patient to fresh air. Supplemental oxygen may be indicated. Assure mucous does not obstruct airway. Call Physician.
INGESTION: Do not induce vomiting call a physician immediately. Remove stomach contents by gastric suction.
- E. ANIMAL TOXICITY DATA:**
Oral LD₅₀ (rat): 450 mg/ Kg (anhydrous)

SECTION VII**SPECIAL PRECAUTIONS & SPILL/ LEAK PROCEDURES**

HANDLING AND STORAGE: Keep containers closed and away from oxidizing agents. Store only in shipping container: Pails (PVC), Drums (Polyethylene) and Mini Bulk tanks (Polyethylene). Bulk material should be stored in Polyethylene Tanks with PVC fittings.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED: It is necessary to contain spill into the smallest area possible by diking, etc. Replace liquid into plastic container. If liquid is absorbed onto dry carrier such as soil or absorbent material, then this material should be held in a dry contained area.

WASTE DISPOSAL METHODS: Liquid should be applied to the soil as a fertilizer not to exceed 3 gallons per acre. Product absorbed onto dry carrier should be applied to soil as a fertilizer not to exceed 50 lbs. per acre.

SECTION VIII**SPECIAL PROTECTION / CONTROL MEASURES**

RESPIRATORY PROTECTION: As required by emergency situation, use an OSHA or NIOSH approved respirator.

VENTILATION: Work outdoors in the open or well ventilated area with this product.

PROTECTIVE GLOVES: Use butyl rubber gloves.

WORK/ HYGIENIC PRACTICES: Wash thoroughly after handling. Also wash clothing.

SECTION IX**ENVIRONMENTAL EFFECTS DATA**

The available data on this plant nutrient material does not indicate any undue hazard to the environment under anticipated use and storage. Any waste due to spillage or leakage should be contained and disposed of as a Fertilizer (see above under Waste Disposal Methods). If discharged into the marine environment it may be toxic to fish and other marine organisms. Due to its nutrient value, may contribute to eutrophication in bodies of water.

SECTION X**TRANSPORTATION DATA**

DOT HAZARD CLASS: CORROSIVE LIQUID

PLACARD: Yes

USDOT Proper Shipping Name: FERROUS CHLORIDE MIXTURE

CLASS 8, NA1760, PGIII

MICRO PLUS IRON

IATA Proper Shipping Name: N/ A

IMO Proper Shipping Name: N/ A

Stoller Enterprises, Inc., believes the information contained in this material safety data sheet is accurate based on the information supplied by reputable suppliers of our raw materials. The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.